## NSN 5320-01-292-1456

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-292-1456 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Natural **Fastener Length:** Between 0.440 inches and 0.460 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.3536 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.130 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

## NSN 5320-01-292-1456

Pin-rivet - Page 2 of 2



ι	Jn	it	Of	Measure:	•

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.