

View Online at <https://aerobasegroup.com/nsn/5320-01-292-5009>

**Fastener Length:**

Between 2.102 inches and 2.132 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.3725 inches and 0.3745 inches

**Head Major Diameter:**

Between 0.752 inches and 0.762 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 1.095 inches and 1.156 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c stem and 43.0 rockwell c stem

**Shear Strength:**

19500 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4130 body or steel comp 4140 body or steel comp 8740 body

**Material Specification:**

Qq-s-763 federal specification all material responses sleeve

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.