## NSN 5320-01-292-5009

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-292-5009

Fastene	r I er	ath:
газіспе	LEI	ıuıı.

Between 2.102 inches and 2.132 inches

**Head Style:** 

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:** 

Between 0.3725 inches and 0.3745 inches

**Head Major Diameter:** 

Between 0.752 inches and 0.762 inches

**Expansion Device:** 

Serrated stem-type w

**Grip Length:** 

Between 1.095 inches and 1.156 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c stem and 43.0 rockwell c stem

**Shear Strength:** 

19500 double pounds per square inch

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4130 body or steel comp 4140 body or steel comp 8740 body

**Material Specification:** 

Qq-s-763 federal specification all material responses sleeve

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Qq-p-416 type 2 cl 2 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.