NSN 5320-01-292-5009

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-292-5009

Fas	ten	er	م ا	กด	ıth	
газ	LEI	ıeı	ᆫ	ιıu	ıuı	١.

Between 2.102 inches and 2.132 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.3725 inches and 0.3745 inches

Head Major Diameter:

Between 0.752 inches and 0.762 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 1.095 inches and 1.156 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c stem and 43.0 rockwell c stem

Shear Strength:

19500 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4130 body or steel comp 4140 body or steel comp 8740 body

Material Specification:

Qq-s-763 federal specification all material responses sleeve

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.