

View Online at <https://aerobasegroup.com/nsn/5320-01-292-5396>

**Fastener Length:**

0.406 inches

**Head Style:**

Oval/truss

**Head Height:**

Between 0.015 inches and 0.019 inches

**Hole Diameter:**

Between 0.039 inches and 0.044 inches

**Shank Diameter:**

Between 0.058 inches and 0.061 inches

**Shank Style:**

Tubular

**Head Major Diameter:**

0.114 inches

**Hole Depth:**

0.046 inches

**Shear Strength:**

26000 double pounds per square inch

**Special Features:**

It is not necessary to anodize composition 5056-h32 aluminum rivets; aluminum rivets (5056) have a double shear strength of 24000 psi min

**Heat Treatment:**

T-4 solution heat treated or h-32 strain hardened

**Material:**

Aluminum alloy 2117 or aluminum alloy 5056

**Material Specification:**

Qq-a-430 federal specification all material responses

**Surface Treatment:**

Anodize or chromate

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.