NSN 5320-01-292-7529

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-292-7529



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.697 inches and 0.717 inches

Head Style:

Err-090

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2641 inches and 0.2651 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.412 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.312 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

125000 single pounds per square inch

Material:

Steel comp 431

Material Specification:

Ams 5628 assn standard single material response or mil-s-18732 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-01-292-7529

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

