# NSN 5320-01-292-7532

Pin-rivet - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.323 inches and 1.343 inches

### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2641 inches and 0.2651 inches

#### Shank Style:

### Head Major Diameter:

0.412 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

0.938 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## Shear Strength:

125000 single pounds per square inch

### Material:

Steel comp 431

# Material Specification:

Ams 5628 assn standard single material response or mil-s-18732 military specification single material response

# Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---



# NSN 5320-01-292-7532

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

