## NSN 5320-01-292-8799



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-292-8799 Fastener Length: 0.506 inches **Head Style:** Undercut pan no. 2 **Head Height:** Between 0.131 inches and 0.141 inches **Shank Diameter:** Between 0.310 inches and 0.312 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.480 inches and 0.522 inches **Expansion Device:** Serrated stem-type w

**Grip Length:** 

Between 0.219 inches and 0.282 inches

Min. Tensile Strength (psi):

5200 pounds per square inch

Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

**Shear Strength:** 

8500 single pounds per square inch

Material:

Steel comp 8740 stem or steel comp 8740 stem

**Material Specification:** 

Astm a331, uns g40120 through g47200 assn standard all material responses stem

**Surface Treatment:** 

Cadmium stem

**Surface Treatment Specification:** 

Qq-p-416, type 1, class 3 federal specification single treatment response stem

**Specification Data:** 

96906-ms90354 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A040a0