## NSN 5320-01-293-5364

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-293-5364

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.690 inches and 1.710 inches
Head Style:
Err-090
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.1890 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
0.3813 inches
Lubrication:
Solid film and cetyl alcohol, specification 305, hi-shear corp
End Application:
Wsd: aircraft, hornet f/a-18
Grip Length:
1.375 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.190 inches
Shear Strength:
95000 single pounds per square inch
Countersink Angle:
100.0 degrees
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:

Unjf

## NSN 5320-01-293-5364

Pin-rivet - Page 2 of 2



	<b>L</b> -	11		ife	_
3	ne	п	_	пe	Ξ

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0