
## NSN 5320-01-293-7967

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.615 inches and 1.635 inches

## Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.078 inches

## Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3110 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.475 inches and 0.505 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

1.130 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.312 inches

## Shear Strength:

132000 single pounds per square inch

## Material:

Steel comp h11

## Material Specification:

Ams 6487 assn standard single material response

#### **Surface Treatment:**

Nickel

## Surface Treatment Specification:

Ams 2416 assn standard single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-01-293-7967

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

