NSN 5320-01-293-7968

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-293-7968 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.990 inches and 2.010 inches **Head Style:** Err-090 **Head Height:** Between 0.098 inches and 0.112 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style: Head Major Diameter:** 0.502 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** W/s: aircraft, stratolifter c-135 **Grip Length:** 1.500 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5320-01-293-7968

Pin-rivet - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.