NSN 5320-01-294-3110

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-294-3110 **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches **Shank Diameter:** Between 0.2470 inches and 0.2495 inches **Shank Style:** Err-090 **Head Major Diameter:** 0.412 inches **Grip Length:** Between 0.126 inches and 0.188 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Special Features:** Head marking: pentagon Material: Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4130 or steel comp 3135 or steel comp 4140 or steel comp e4340 or steel comp 4037 **Material Specification:** Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6758 military specification 4th material response or ams 6330 assn standard 5th material response or mil-s-5626 military specification 6th material response or mil-s-5000 military specification 7th material response or mil-s-8695 military specification 8th material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Specification Data:** 80205-nas1054 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

Mil-s-6098 spec.

Mil-std (military Standard):

A528u0