NSN 5320-01-294-6817

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-294-6817

Identification Code Color:
Black
Fastener Length:
0.203 inches
Head Style:
Oval/truss
Head Height:
Between 0.015 inches and 0.019 inches
Hole Diameter:
Between 0.039 inches and 0.044 inches
Shank Diameter:
Between 0.058 inches and 0.061 inches
Shank Style:
Tubular
Head Major Diameter:
Between 0.104 inches and 0.114 inches
Hole Depth:
0.046 inches
Shear Strength:
35000 double pounds per square inch
Special Features:
Special Features: Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper)
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper)
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material:
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification:
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses Surface Treatment:
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses Surface Treatment: Oxide
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses Surface Treatment: Oxide Surface Treatment Specification:
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses Surface Treatment: Oxide Surface Treatment Specification: Mil-f-496 military specification single treatment response
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses Surface Treatment: Oxide Surface Treatment Specification: Mil-f-496 military specification single treatment response Shelf Life:
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses Surface Treatment: Oxide Surface Treatment Specification: Mil-f-496 military specification single treatment response Shelf Life: N/a
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses Surface Treatment: Oxide Surface Treatment Specification: Mil-f-496 military specification single treatment response Shelf Life: N/a
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses Surface Treatment: Oxide Surface Treatment Specification: Mil-f-496 military specification single treatment response Shelf Life: N/a Unit Of Measure:
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses Surface Treatment: Oxide Surface Treatment Specification: Mil-f-496 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses Surface Treatment: Oxide Surface Treatment Specification: Mil-f-496 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No
Optional design, 0.042 to 0.046 in. Hole dia; 0.042 in. Hole depth (taper) Material: Copper alloy 260 or copper alloy 270 Material Specification: Qq-w-321 federal specification all material responses Surface Treatment: Oxide Surface Treatment Specification: Mil-f-496 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: