## NSN 5320-01-294-9488

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-294-9488 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.237 inches and 1.257 inches **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2646 inches and 0.2651 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.812 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Thread Size:** 0.250 inches Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258, cagec, 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

Unit Of Measure:

N/a

## NSN 5320-01-294-9488

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.