
# NSN 5320-01-294-9495

Pin-rivet - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.038 inches and 1.058 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.2021 inches and 0.2026 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

0.688 inches

#### Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.190 inches

#### Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp 431

## Material Specification:

Ams 5628 assn standard single material response or mil-s-18732 military specification single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Hi-shear spec. 258, cagec 73197 mfr ref single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

---



# NSN 5320-01-294-9495

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

