
# NSN 5320-01-296-2084

Pin-rivet - Page 1 of 2





# Thread Class: 3a

Thread Direction:

Right-hand

### Fastener Length:

Between 1.510 inches and 1.530 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.3948 inches

# End Application:

W/s: aircraft, eagle f-15

## Grip Length:

1.130 inches

#### Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### Countersink Angle:

100.0 degrees

#### **Special Features:**

White paint on head

#### Material:

Steel comp xm-13

#### **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Hi-shear spec. 258, cagec 73197 mfr ref single treatment response

### **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-296-2084

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

