

View Online at <https://aerobasegroup.com/nsn/5320-01-299-2925>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.385 inches and 1.405 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.077 inches and 0.090 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2646 inches and 0.2651 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.415 inches and 0.440 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

1.010 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Shear Strength:**

125000 single pounds per square inch

**Material:**

Steel comp 431

**Material Specification:**

Mil-s-18732 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Hi-shear process spec. 258, caged 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-18732 spec.