
# NSN 5320-01-299-6648

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.127 inches and 1.147 inches

## Head Style:

Err-090

#### Head Height:

Between 0.064 inches and 0.074 inches

### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

### Shank Diameter:

Between 0.2177 inches and 0.2182 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.370 inches and 0.390 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

0.817 inches

# Thready Qty Per Inch (tpi):

32

# Thread Size:

0.190 inches

# Shear Strength:

125000 single pounds per square inch

## Material:

Steel comp 431

## Material Specification:

Mil-s-18732 military specification single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

258, cagec 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5320-01-299-6648

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

