# NSN 5320-01-300-3714

Pin-rivet - Page 1 of 2





### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.815 inches and 0.835 inches

## Head Style:

Err-090

#### **Head Height:**

Between 0.045 inches and 0.055 inches

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

### Shank Diameter:

Between 0.2172 inches and 0.2182 inches

### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.295 inches and 0.315 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

0.505 inches

# Thready Qty Per Inch (tpi):

32

# Thread Size:

0.190 inches

## Shear Strength:

125000 single pounds per square inch

## Material:

Steel comp 431

## **Material Specification:**

Mil-s-18732 military specification single material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

# **Thread Series Designator:**

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-300-3714

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

