# NSN 5320-01-301-4099

Pin-rivet - Page 1 of 2





Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.159 inches and 1.199 inches

## Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.088 inches

## Width Between Flats:

Between 0.1582 inches and 0.1617 inches

### Shank Diameter:

Between 0.3735 inches and 0.3745 inches

#### Shank Style:

Head Major Diameter:

Between 0.563 inches and 0.583 inches

## Grip Length:

Between 0.626 inches and 0.688 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.375 inches

#### Shear Strength:

156000 single pounds per square inch

Material:

Steel comp h11

## **Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

## Surface Treatment Specification:

Ams 2416 assn standard single treatment response

## **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas4450 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-301-4099

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

