NSN 5320-01-302-7702

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-302-7702 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.003 inches and 1.023 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2177 inches and 0.2182 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.370 inches and 0.390 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.693 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258, cagec, 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

__

Unit Of Measure:

NSN 5320-01-302-7702

Pin-rivet - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.