# NSN 5320-01-302-9955

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-302-9955



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 1.260 inches and 1.280 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

0.885 inches

#### Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## Shear Strength:

125000 single pounds per square inch

## Material:

Steel comp 431

# Material Specification:

Mil-s-18732 military specification single material response

## Surface Treatment:

Passivate

# Surface Treatment Specification:

Hi-shear spec. 258, cagec 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-302-9955

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

