

View Online at <https://aerobasegroup.com/nsn/5320-01-303-1637>

Fastener Length:

0.844 inches

Head Style:

Tapered pan

Head Height:

Between 0.130 inches and 0.140 inches

Shank Diameter:

Between 0.258 inches and 0.260 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.400 inches and 0.432 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.594 inches and 0.657 inches

Min. Tensile Strength (psi):

112000 pounds per square inch

Hardness Rating:

326.0 knoop and 466.0 knoop sleeve

Special Features:

Single action fastener without frangible type of locking collar or locking collar cap

Material:

Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4620 or steel comp 4815 or steel comp 6150 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740

Material Specification:

Astm a331 assn standard all material responses

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, ty i, cl 3 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0