

View Online at <https://aerobasegroup.com/nsn/5320-01-303-3929>

Fastener Length:

0.928 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.197 inches and 0.199 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.386 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.719 inches and 0.782 inches

Min. Tensile Strength (psi):

112000 pounds per square inch

Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Single action fastener without frangible type of locking collar or locking collar cap

Material:

Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4620 or steel comp 4815 or steel comp 6150 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740

Material Specification:

Astm a331 assn standard all material responses

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, ty i, cl 3 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0