

View Online at <https://aerobasegroup.com/nsn/5320-01-303-3930>

**Fastener Length:**

0.344 inches

**Head Style:**

Tapered pan

**Head Height:**

Between 0.130 inches and 0.140 inches

**Shank Diameter:**

Between 0.258 inches and 0.260 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.400 inches and 0.432 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.094 inches and 0.157 inches

**Min. Tensile Strength (psi):**

112000 pounds per square inch

**Hardness Rating:**

326.0 knoop and 466.0 knoop sleeve

**Special Features:**

Single action fastener without frangible type of locking collar or locking collar cap

**Material:**

Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4620 or steel comp 4815 or steel comp 6150 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740

**Material Specification:**

Astm a331 assn standard all material responses

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, ty i, cl 3 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0