## NSN 5320-01-304-4477

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.910 inches and 1.930 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

## Shank Diameter:

Between 0.3891 inches and 0.3901 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.5554 inches and 0.5604 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

1.340 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.375 inches

#### Shear Strength:

95000 single pounds per square inch

## **Countersink Angle:**

100.0 degrees

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

## Surface Treatment Specification:

294, cagec 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-304-4477

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

