

View Online at <https://aerobasegroup.com/nsn/5320-01-304-6084>

Fastener Length:

1.281 inches

Head Style:

Straight pan

Head Height:

Between 0.130 inches and 0.140 inches

Shank Diameter:

Between 0.258 inches and 0.260 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.400 inches and 0.432 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 1.031 inches and 1.095 inches

Min. Tensile Strength (psi):

112000 pounds per square inch

Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

Special Features:

No lubrication, except manufacturer's option to lubricate lock mechanism with lox compatible dry film lubricant; the "u" in the p/n denotes single action fasteners installed with a single action tool

Material:

Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4620 or steel comp 4815 or steel comp 6150 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740

Material Specification:

Astma 331 assn standard single material response

Surface Treatment:

Cadmium sleeve and chromate sleeve or aluminum alloy sleeve

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0