NSN 5320-01-305-0142

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-305-0142

| view Offilite at https://derobasegroup.com/hsr//5520-61-5005-61-42 |
|---|
| Shank Diameter: |
| Between 0.1970 inches and 0.1990 inches |
| Head Major Diameter: |
| 0.310 inches |
| Features Provided: |
| Drive nut |
| Material: |
| Steel comp 303 sleeve or steel comp 304 sleeve or steel comp 303se sleeve |
| Material Specification: |
| Qq-a-225/9, t6 federal specification single material response nut |
| Surface Treatment: |
| Passivate sleeve and cadmium sleeve or passivate sleeve and cadmium sleeve and chromate sleeve |
| Surface Treatment Specification: |
| Qq-p-35 federal specification 1st treatment response sleeve and qq-p-416, type 1, cl 3 federal specification 1st treatment response sleeve or |
| qq-p-35 federal specification 2nd treatment response sleeve and qq-p-416, type 2, cl 3 federal specification 2nd treatment response sleeve |
| Specification Data: |
| 80205-nas1674 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-a-8625 spec. |
| |
| |