# NSN 5320-01-305-0819

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-305-0819

## Fastener Length:

Between 0.927 inches and 0.947 inches

## Head Style:

Undersized oval countersunk

# Head Height:

Between 0.003 inches and 0.005 inches

## Shank Diameter:

Between 0.124 inches and 0.127 inches

#### Shank Style:

Straight w/radius chamfered tip

#### Head Major Diameter:

0.1957 inches

#### Head Minor Diameter:

0.134 mils

#### **Countersink Height:**

0.0286 inches

# Shear Strength:

26000 single pounds per square inch

#### **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

## **Special Features:**

Rivets maybe furnished with plain ends or chamfered ends

# Heat Treatment:

T-4 solution heat treated

Material:

Aluminum alloy 2117

#### **Material Specification:**

Qq-a-430, t4 federal specification single material response

#### Surface Treatment:

Anodize or chromate

#### Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

#### Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A040a0

#### Mil-std (military Standard):

Mil-a-8625 spec.