NSN 5320-01-305-0821

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-305-0821 Fastener Length: Between 0.677 inches and 0.697 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.003 inches and 0.005 inches **Shank Diameter:** Between 0.124 inches and 0.127 inches **Shank Style:** Straight w/radius chamfered tip **Head Major Diameter:** 0.1957 inches **Head Minor Diameter:** 0.134 mils **Countersink Height:** 0.0286 inches **Shear Strength:** 26000 single pounds per square inch **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Special Features:** Rivets maybe furnished with plain ends or chamfered ends **Heat Treatment:** T-4 solution heat treated Material: Aluminum alloy 2117 **Material Specification:** Qq-a-430, t4 federal specification single material response **Surface Treatment:** Anodize or chromate **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A040a0

Mil-a-8625 spec.

Mil-std (military Standard):