## NSN 5320-01-305-5542



Pin-rivet Collar - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-305-5542 **Thread Class: Thread Direction:** Right-hand **Collar Outside Diameter:** Between 0.303 inches and 0.307 inches Collarheight: Between 0.437 inches and 0.457 inches Lubrication: Solid film **Collar Inside Diameter:** Between 0.195 inches and 0.200 inches **Features Provided:** Washer Thready Qty Per Inch (tpi): **Thread Size:** 0.190 inches Collar Style: Threaded (break off) type Material: Steel comp 301 washer or steel comp 302b washer or steel comp 302 washer or steel comp 303 washer or steel comp 303 plus cb washer or steel comp 303 plus x washer or steel comp 303f washer or steel comp 303f plus cb washer or steel comp 303s washer or steel comp 303se washer or steel comp 304 washer or steel comp 304l washer or steel comp 305 washer or steel comp 308 washer or steel comp 309 washer or steel comp 309s washer or steel comp 310 washer or steel comp 310s washer or steel comp 314 washer or steel comp 316 washer or steel comp 316l washer or steel comp 321 washer or steel comp 321 washer or steel comp 324 washer or steel comp 324 washer or steel comp 326 washer or steel comp 326 washer or steel comp 326 washer or steel comp 327 washer or steel comp 327 washer or steel comp 328 washer or steel comp or steel comp 325 washer or steel comp 330 washer or steel comp 340 washer or steel comp 347 washer or steel comp 348 washer or steel comp 384 washer or steel comp 385 washer **Surface Treatment:** Passivate washer **Surface Treatment Specification:** Hi-shear spec. 258, cagec 73197 mfr ref single treatment response washer **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

Fiig:

A530g0

**Demilitarization:**