

View Online at <https://aerobasegroup.com/nsn/5320-01-305-5542>

Thread Class:

3b

Thread Direction:

Right-hand

Collar Outside Diameter:

Between 0.303 inches and 0.307 inches

Collarheight:

Between 0.437 inches and 0.457 inches

Lubrication:

Solid film

Collar Inside Diameter:

Between 0.195 inches and 0.200 inches

Features Provided:

Washer

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Collar Style:

Threaded (break off) type

Material:

Steel comp 301 washer or steel comp 302b washer or steel comp 302 washer or steel comp 303 washer or steel comp 303 plus cb washer or steel comp 303 plus x washer or steel comp 303f washer or steel comp 303f plus cb washer or steel comp 303s washer or steel comp 303se washer or steel comp 304 washer or steel comp 304l washer or steel comp 305 washer or steel comp 308 washer or steel comp 309 washer or steel comp 309s washer or steel comp 310 washer or steel comp 310s washer or steel comp 314 washer or steel comp 316 washer or steel comp 316l washer or steel comp 317 washer or steel comp 321 washer or steel comp 323 washer or steel comp 324 washer or steel comp 325 washer or steel comp 330 washer or steel comp 330a washer or steel comp 347 washer or steel comp 348 washer or steel comp 384 washer or steel comp 385 washer

Surface Treatment:

Passivate washer

Surface Treatment Specification:

Hi-shear spec. 258, caged 73197 mfr ref single treatment response washer

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530g0