

View Online at <https://aerobasegroup.com/nsn/5320-01-306-3555>

**Fastener Length:**

0.281 inches

**Head Style:**

Universal

**Head Height:**

Between 0.054 inches and 0.064 inches

**Shank Diameter:**

Between 0.139 inches and 0.143 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.238 inches and 0.262 inches

**Expansion Device:**

Plain stem-type t

**Grip Length:**

Between 0.063 inches and 0.125 inches

**Special Features:**

Monel lock ring for mechanically locked spindle

**Heat Treatment:**

T-62 solution heat treated sleeve

**Material:**

Nickel alloy 600 stem

**Material Specification:**

Ams 5665 assn standard single material response stem

**Surface Treatment:**

Anodize sleeve or chromate sleeve

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response sleeve

**Specification Data:**

80205-nas1738 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.