NSN 5320-01-306-9618

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-306-9618 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.790 inches and 2.810 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style: Head Major Diameter:** Between 0.554 inches and 0.560 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 2.255 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 45.0 rockwell c and 48.0 rockwell c **Thread Size:** 0.375 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, type 2 cl 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-01-306-9618

Pin-rivet - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.