## **NSN 5320-01-307-1769**Blind Rivet - Page 1 of 1



Head Major Diameter:  0.696 inches  Features Provided: Drive nut  Hardness Rating: 39.0 rockwell c nut and 43.0 rockwell c nut  Material: Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut  Material Specification: Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-60 specification 3rd material response nut  Surface Treatment: Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	19 military
Between 0.3725 inches and 0.3745 inches  Head Major Diameter: 0.696 inches  Features Provided: Drive nut  Hardness Rating: 39.0 rockwell c nut and 43.0 rockwell c nut  Material: Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut  Material Specification: Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-60 specification 3rd material response nut  Surface Treatment: Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	19 military
Features Provided: Drive nut Hardness Rating: 39.0 rockwell c nut and 43.0 rockwell c nut Material: Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut Material Specification: Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-60 specification 3rd material response nut Surface Treatment: Passivate sleeve and cadmium sleeve Surface Treatment Specification:	19 military
Features Provided: Drive nut  Hardness Rating: 39.0 rockwell c nut and 43.0 rockwell c nut  Material: Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut  Material Specification: Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-60 specification 3rd material response nut  Surface Treatment: Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	19 military
Drive nut  Hardness Rating:  39.0 rockwell c nut and 43.0 rockwell c nut  Material:  Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut  Material Specification:  Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-60 specification 3rd material response nut  Surface Treatment:  Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	19 military
Hardness Rating:  39.0 rockwell c nut and 43.0 rockwell c nut  Material:  Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut  Material Specification:  Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-60 specification 3rd material response nut  Surface Treatment:  Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	19 military
39.0 rockwell c nut and 43.0 rockwell c nut  Material:  Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut  Material Specification:  Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-60 specification 3rd material response nut  Surface Treatment:  Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	19 military
Material: Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut  Material Specification: Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-60 specification 3rd material response nut  Surface Treatment: Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	19 military
Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut  Material Specification:  Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-60 specification 3rd material response nut  Surface Treatment:  Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	49 military
Material Specification:  Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-60 specification 3rd material response nut  Surface Treatment:  Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	49 military
Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-60 specification 3rd material response nut  Surface Treatment:  Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	49 military
specification 3rd material response nut  Surface Treatment:  Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	49 military
Surface Treatment: Passivate sleeve and cadmium sleeve Surface Treatment Specification:	
Passivate sleeve and cadmium sleeve  Surface Treatment Specification:	
Surface Treatment Specification:	
Qq-p-416, type 2, cl 2 federal specification single treatment response nut	
Specification Data:	
80205-nas1670 professional/industrial association standard	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A040a0	
Mil-std (military Standard):	
Mil-s-6758 spec.	