

View Online at <https://aerobasegroup.com/nsn/5320-01-310-3456>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.340 inches and 1.465 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.200 inches and 0.202 inches

Shank Style:

Pin rivet, threaded

Head Major Diameter:

0.386 inches

Lubrication:

Cetyl alcohol

End Application:

Vertical stab; f/a-18e/f hornet aircraft

Grip Length:

Between 0.501 inches and 0.562 inches

Thready Qty Per Inch (tpi):

56

Thread Size:

0.104 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Fastener, adjustable preload-self sustaining-positive lock, 100 degree flush head installed with flush and protruding sleeves; nickel-electro plate (cl-ii)

Material:

Steel comp 8740 sleeve

Material Specification:

Qq-a-430 federal specification single material response collar

Surface Treatment:

Cadmium sleeve and chromate sleeve

Surface Treatment Specification:

Qq-p-416, type ii, class2 federal specification single treatment response mandrel

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-5541 spec.