# NSN 5320-01-311-4073

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-311-4073



# Thread Class: 3a

Thread Direction:

Right-hand

# Fastener Length:

Between 2.160 inches and 2.220 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

0.078 inches

#### Shank Diameter:

Between 0.2005 inches and 0.2025 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.386 inches

#### Lubrication:

Cetyl alcohol

#### Grip Length:

Between 1.313 inches and 1.375 inches

# Thready Qty Per Inch (tpi):

56

# Min. Tensile Strength (psi):

95000 pounds per square inch

#### **Thread Size:**

0.164 inches

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Special Features:**

Hex socket in head

#### Material:

Titanium alloy uns r56400

# Material Specification:

Ams 4967 assn standard single material response

#### **Thread Series Designator:**

Uns

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# NSN 5320-01-311-4073

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

