NSN 5320-01-311-6335

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-311-6335

Fastener Length:
0.756 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.469 inches and 0.532 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.634 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.469 inches and 0.532 inches
Min. Tensile Strength (psi):
112000 pounds per square inch
Hardness Rating:
48.0 rockwell c stem and 53.0 rockwell c stem
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
"u" denotes single action fasteners installed with a single action tool
Material:
Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp
4340 or steel comp 4620 or steel comp 4815 or steel comp 6150 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel
comp 8640 or steel comp 8740
Material Specification:
Astm a331 assn standard single material response
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0