
NSN 5320-01-311-9403

Pin-rivet - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand** Fastener Length: Between 0.760 inches and 0.780 inches Head Style: Countersunk w/reverse chamfer **Head Height:** Between 0.1160 inches and 0.1230 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches Shank Diameter: Between 0.2490 inches and 0.2495 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.5018 inches and 0.5066 inches Lubrication: Cetyl alcohol Grip Length: 0.380 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 6650 pounds per square inch **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Special Features:** Injection hole 0.120 in. Lg located 0.150 in. From top of head Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

NSN 5320-01-311-9403

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

