NSN 5320-01-311-9404

Pin-rivet - Page 1 of 2

Thread Class:

3a



View Online at https://aerobasegroup.com/nsn/5320-01-311-9404

ou .
Thread Direction:
Right-hand
Fastener Length:
Between 0.885 inches and 0.905 inches
Head Style:
Countersunk w/reverse chamfer
Head Height:
Between 0.1060 inches and 0.1230 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.5018 inches and 0.5066 inches
Lubrication:
Cetyl alcohol
Grip Length:
0.505 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
6650 pounds per square inch
Thread Size:
0.250 inches
Countersink Angle:
100.0 degrees
Special Features:
Injection hole 0.120 in. Lg located 0.180 in. From top of head
Material:
Material: Steel comp xm-13
Steel comp xm-13
Steel comp xm-13 Material Specification:
Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response
Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment:
Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate
Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response

NSN 5320-01-311-9404

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0