## NSN 5320-01-311-9406

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-311-9406 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.115 inches and 1.135 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.1430 inches and 0.1500 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.6287 inches and 0.6335 inches Lubrication: Solid film and cetyl alcohol **Grip Length:** 0.630 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 9200 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 14600 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-311-9406

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0