NSN 5320-01-311-9407

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-311-9407 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.885 inches and 0.905 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.1160 inches and 0.1230 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.5018 inches and 0.5066 inches Lubrication: Cetyl alcohol **Grip Length:** 0.505 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 6650 pounds per square inch **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Special Features:** Injection hole 0.120 in. Lg. Located 0.270 in. From top of head Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:**

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

NSN 5320-01-311-9407

Pin-rivet - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0