# NSN 5320-01-313-1400

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-313-1400



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Identification Code Color:

Blue

#### Fastener Length:

Between 0.885 inches and 0.905 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2641 inches and 0.2651 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.495 inches and 0.505 inches

## Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

95000 pounds per square inch

#### **Thread Size:**

0.250 inches

## Shear Strength:

10490 double pounds per square inch

## Countersink Angle:

100.0 degrees

#### Material:

Titanium alloy uns r54520

## Material Specification:

Ams4967 mfr ref single material response

## **Thread Series Designator:**

Unjf

# Specification Data:

73197-hl111vf-8-8 manufacturers standard

# Shelf Life:

N/a

# NSN 5320-01-313-1400

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

