

View Online at <https://aerobasegroup.com/nsn/5320-01-314-5557>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.010 inches and 1.030 inches

Head Style:

Err-090

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.630 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

260000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

156000 single pounds per square inch

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837, type 2, cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.