

View Online at <https://aerobasegroup.com/nsn/5320-01-315-0248>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.573 inches and 0.593 inches

Head Style:

Err-090

Head Height:

Between 0.059 inches and 0.061 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.390 inches and 0.395 inches

Lubrication:

Cetyl alcohol

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Grip Length:

Between 0.183 inches and 0.193 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Iron alloy 660

Material Specification:

Ams5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0