NSN 5320-01-315-3589



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-315-3589 **Identification Code Color:** Green **Fastener Length:** 0.905 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.162 inches and 0.164 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** 0.333 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.719 inches and 0.782 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem **Shear Strength:** 112000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 6150 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 **Material Specification:** Astm a331 assn standard all material responses **Surface Treatment:** Cadmium stem or aluminum stem **Surface Treatment Specification:** Qq-p-416, type 1, class 3 federal specification 1st treatment response stem or mil-c-83488 military specification 2nd treatment response stem Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Mil-std (military Standard):

Mil-c-83488 spec.

Fiig: A040a0