# NSN 5320-01-315-4236

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-315-4236



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 1.065 inches and 1.085 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.0450 inches and 0.0550 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.2950 inches and 0.3150 inches

### Grip Length:

0.750 inches

Thready Qty Per Inch (tpi):

32

### Thread Size:

0.190 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Threads are color coded black

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Hi-kote 1, cagec 73197 mfr ref single treatment response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-315-4236

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

