## NSN 5320-01-315-5823



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-315-5823 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.596 inches and 0.616 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2564 inches and 0.2612 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 95000 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Iron alloy **Material Specification:** Ams5737 mfr ref single material response **Surface Treatment: Passivate Thread Series Designator:** Unjc **Specification Data:** 73197-hl407-5-4 manufacturers standard Shelf Life:

N/a **Unit Of Measure:** 

## NSN 5320-01-315-5823

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0