NSN 5320-01-315-5824

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Identification Code Color:

За

Blue



View Online at https://aerobasegroup.com/nsn/5320-01-315-5824

Fastener Length:
Between 0.697 inches and 0.717 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2641 inches and 0.2651 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.3898 inches and 0.3948 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.307 inches and 0.317 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
95000 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
10490 double pounds per square inch
Countersink Angle:
100.0 degrees
Material:
Titanium alloy uns r54520
Material Specification:
Ams4967 mfr ref single material response
Thread Series Designator:
Unjf
Specification Data:
73197-hl111vf-8-5 manufacturers standard
Shelf Life:
N/a

NSN 5320-01-315-5824

Pin-rivet - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0