NSN 5320-01-315-9286

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Identification Code Color:

За

Blue



View Online at https://aerobasegroup.com/nsn/5320-01-315-9286

Fastener Length:								
Between 0.635 inches and 0.655 inches								
Head Style:								
Flush countersunk								
Width Between Flats:								
Between 0.0947 inches and 0.0967 inches								
Shank Diameter:								
Between 0.2641 inches and 0.2651 inches								
Shank Style:								
Pin-rivet, straight, threaded								
Head Major Diameter:								
Between 0.5018 inches and 0.5066 inches								
Lubrication:								
Cetyl alcohol, specification 305, hi-shear corp								
Grip Length:								
Between 0.245 inches and 0.255 inches								
Thready Qty Per Inch (tpi):								
28								
Min. Tensile Strength (psi):								
160000 pounds per square inch								
Thread Size:								
0.250 inches								
Shear Strength:								
10490 double pounds per square inch								
Countersink Angle:								
100.0 degrees								
Material:								
Titanium alloy uns r54520								
Material Specification:								
Ams4967 mfr ref single material response								
Thread Series Designator:								
Unjf								
Specification Data:								
73197-hl113vf-8-4 manufacturers standard								
Shelf Life:								
N/a								

NSN 5320-01-315-9286

Pin-rivet - Page 2 of 2



ı	1	n	iŧ	1	: N/	lea			_	
ı	u	n	IT	OI	١V	ıea	เรเ	JI	е	:

--

Demilitarization:

No

Fiig:

A528u0